



REFERENCE: A.S.F. 1-8985
 CONSTRUCTION POINT GAUGE
 FOR
 RIDE CONTROL &
 SUPER SERVICE RIDE CONTROL
 TRUCK BOLSTER POCKETS
 70, 100 & 125 TON

TOLERANCE:
 "A" +/- .005"
 DIMENSIONED ANGLES +/- .5 DEGREES

A.A.R. STANDARD M-214 ACCEPTANCE:
 CONSTRUCTION POINT +1/8", -1/16"

RECERTIFICATION WEAR LIMIT ALLOWANCE +/- .020"
 REFERENCE:
 AAR D MANUAL
 M-214

Material:
 304 Stainless Steel
 Thickness: .125"

RIDE CONTROL

GAGE	TYPE OF TRUCK	"A"	"B"
W841-1	70 TON-ALL DESIGNS 70 TON LOW LEVEL - 5' -3" WHEELBASE	12.750	17.500
W841-2	100 TON - 7 & 8 COILS 125 TON GRADE C ONLY STANDARD ROTATIONAL S LUGS	12.000	16.750
W841-3	100 TON - 9 COIL	12.500	17.250
W841-3	125 TON - GRADE C ONLY WITH WIDE LAND ROTATION	12.500	17.250
W841-4	100 TON SUPER SERVICE R.C.	12.750	17.250
W841-5	70 TON SUPER SERVICE RC	13.000	18.750

WINCHESTER INDUSTRIES INC.				
CONSTRUCTION POINT GAUGE				
SIZE A	Job#	DWG NO. W841	Disk	REV E
CUSTOMER			ENG JDB 01/20/2009	